
NTN BEARING CORPORATION OF AMERICA
Head Office
1501 Woodfield Rd,
Schaumburg, IL 60173
Phone: 847-298-7500
Fax: 847-699-9744
Toll Free: 800-323-2358
Email: mkt@ntnamerica.com
Website: www.ntnamericas.com

Item # UCUP206D1






Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC206D1
Housing Number	UP206D1
Housing Material	Steel
End Type	Open
Performance	Light Duty
Dynamic Load Rating	4384 lbf 19500 N 19.50 kN
Static Load Rating	2540 lbf 11300 N 11.30 kN
Rotational Speed [Max]	4900 RPM
Weight	2.426 lb 1.100 kg
Operating Temperature Range	-40 to 250 °F -40 to 120 °C
Lubrication	Outer Ring Relubricatable

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Dimensional Specifications



Pillow Block Unit, Set Screw, Narrow Style, UCUP Type - Dimensions

d	1.1810 in 30.000 mm
J	2.5937 in 66.0 mm
L	3.6875 in 94.0 mm
A	1.8750 in 48.0 mm
H	1.6875 in 42.9 mm
H1	0.4687 in 12.0 mm
H2	3.3125 in 84.0 mm
N	M14x2
j	0.7187 in 18.0 mm
B	1.5000 in 38.100 mm
S	0.6260 in 15.900 mm
F	0.1811 in 4.600 mm

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Lubrication	Outer Ring
Ball Material	Through Hardened
Outside Diameter	2.4410 in 62.000 mm
Outside Diameter	2.4410 in 62.000 mm
Bore Type	Cylindrical
Outside Ring Width	0.7480 in 19.000 mm
Inside Ring Width	1.5000 in 38.100 mm
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	4384 lbf 19500 N

Radial Static Load Rating	2540 lbf 11300 N
Rotational Speed [Max]-Grease	4850 RPM

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES