NTN BEARING CORPORATION OF AMERICA
Head Office
1501 Woodfield Rd,
Schaumburg, IL 60173
Phone: 847-298-7500
Fax: 847-699-9744
Toll Free: 800-323-2358
Email: mkt@ntnamerica.com
Website: www.ntnamericas.com

Item # UCP214D1




Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC214D1
Housing Number	P214D1
Housing Material	Cast Iron
Housing Construction	1 Piece
Performance	Light Duty
End Type	Open
Dynamic Load Rating	13938 lbf 62000 N 62.00 kN
Static Load Rating	9892 lbf 44000 N 44.00 kN
Rotational Speed [Max]	2300.0 RPM
Weight	14.396 lb 6.530 kg
Operating Temperature Range	-40 to 250 °F -40 to 120 °C
Lubrication	Relubricatable

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Dimensional Specifications



Pillow Block Unit, Cast Housing, Set Screw, UCP/UCPX Type - Dimensions

d	2.7560 in 70.000 mm
J	8.2812 in 210.0 mm
L	10.4687 in 266.0 mm
A	2.8437 in 72.0 mm
H	3.1250 in 79.4 mm
H1	1.0625 in 27.0 mm
H2	6.1875 in 157.0 mm
L1	3.0313 in 77.0 mm
N	0.9687 in 25.0 mm
N1	1.0937 in 28.0 mm
B	2.9370 in 74.600 mm
S	1.1890 in 30.200 mm
F	0.3465 in 8.800 mm

INSUMIND PERÚ
INSUMOS Y REPUESTOS INDUSTRIALES