
Richtlänge Datum length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]
1170 ≤ Ld ≤ 5000	± 2	4
5000 < Ld ≤ 8000	± 4	8
8000 < Ld ≤ 10000	± 6	12
10000 < Ld ≤ 12500	± 8	16
12500 < Ld ≤ 15000	± 10	20
15000 < Ld ≤ 18000	± 13	26

Prinzip-Skizze
Principle sketch



Profil / Section: SPA		
b [mm]	h [mm]	α [°]
12,6 ± 0,8	10,0 +0,9/-0,5	40 ± 2

Aufbau des Riemens:
1. Umhüllungsgewebe
2. SBR/NR Mischung
3. Polyester
4. SBR/NR Mischung


V-Belt construction:
1. Cover fabric
2. SBR/NR compound
3. Polyester
4. SBR/NR compound

Kennzeichnungsbeispiel / Marking example:



Werkscode / Plant code | Profil / Profile | Länge / Length | Jahreszeichen / Year code

Längen-Messbedingungen nach DIN 7753 Teil 1 und ISO 4183
Length measurement according to DIN 7753 Part 1 and ISO 4183



d_d [mm]	143,24 ± 0,05
U_d [mm]	450
d_a [mm]	149 ± 0,05
b_d [mm]	11,00
α [°]	36 ± 10‘
t_{min} [mm]	14
Q [N]	560
$L_d = 2a + U_d$	
$L_a = 2a + U_a$	

Wir beraten Sie gerne über die Produkteigenschaften und -anpassungen bei besonderen Anforderungen. Bitte beachten Sie auch die Hinweise in den Optibelt Dokumentationen. Irrtümer und technische Änderungen vorbehalten. www.optibelt.com, © Optibelt GmbH
We would be pleased to offer advice about technical characteristics and drive design as well as special requirements. Further information can be found in Optibelt documentation. Subject to technical modification and change, errors and omissions excepted. www.optibelt.com, © Optibelt GmbH

optibelt SK S=C Plus

Profil SPA

Zust.	Änderungen	Datum	Name
4			
3			
2			
1	Erstellt	12.02.16	MUr
0	Freigabe	12.02.16	HGr

Dateiname: Datenblatt_optibelt SK S=C Plus_SPA.pdf

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES