
Längenbezeichnung Length designation	Außenlänge Outside length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]
820 – 1900	2083 ≤ La ≤ 4826	± 2	4
1900 – 3000	4826 < La ≤ 7620	± 4	8
3000 – 3750	7620 < La ≤ 9525	± 6	12
3750 – 4500	9525 < La ≤ 11430	± 8	16
4500 – 5000	11430 < La ≤ 12700	± 12	24
5000 – 8620	12700 < La ≤ 20980	± 30	60

Prinzip-Skizze
Principle sketch



Profil / Section: 8V		
b [mm]	h [mm]	α [°]
25,8 ± 0,8	23,0 +1,5/-0,9	40 ± 2

Aufbau des Riemens:
1. Umhüllungsgewebe
2. SBR/NR Mischung
3. Polyester
4. SBR/NR Mischung

V-Belt construction:
1. Cover fabric
2. SBR/NR compound
3. Polyester
4. SBR/NR compound


Kennzeichnungsbeispiel / Marking example:



Werkscode / Plant code — Profil / Profile — Längenbezeichnung / Length designation — Jahreszeichen / Year code

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Längen-Messbedingungen nach RMA/ARPM IP-22
Length measurement according to RMA/ARPM IP-22



U_a [mm]	1000
d_a [mm]	318,30 ± 0,13
b_1 [mm]	25,40 ± 0,13
α [°]	38 ± 15‘
t_{min} [mm]	25,50
Q [N]	1000
$L_a = 2a + U_a$	

Wir beraten Sie gerne über die Produkteigenschaften und -anpassungen bei besonderen Anforderungen. Bitte beachten Sie auch die Hinweise in den Optibelt Dokumentationen. Irrtümer und technische Änderungen vorbehalten. www.optibelt.com, © Optibelt GmbH
We would be pleased to offer advice about technical characteristics and drive design as well as special requirements. Further information can be found in Optibelt documentation. Subject to technical modification and change, errors and omissions excepted. www.optibelt.com, © Optibelt GmbH

optibelt SK S=C Plus

Profil 8V

Zust.	Änderungen	Datum	Name
4			
3			
2			
1	Freigabe	31.03.2016	HGr
0	Erstellt	31.03.2016	Mur

Dateiname: Datenblatt_optibelt SK S=C Plus_8V.pdf