Product Specifications

LF17056



Lube Filter, Cartridge

Fleetguard® LF17056 premium cartridge oil filter is enviromentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

A Frecuencia 2	ISO 4548-12	Largest End Inside Diameter	2.24 inch / 57.00 mm
Flujo Nominal	38.57 gpm / 146.00 L/min	Diámetro Interior De La Junta	2.11 inch / 53.50 mm
Largest Outside Diameter	4.76 inch / 121.00 mm	Válvula De Presión	No
Eficiencia De Partículas Primarias	40.00 micron (c) @ 98.7%	Altura	8.01 in / 203.50 mm
Capacity Test Specification	ISO 4548-12		

Applicable Region	North America, China, Europe, South America, South East Asia, South Pacific

Related Parts

Replaces LF16244

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES