Product Specifications

LF17580



Lube Filter, Spin-On

Fleetguard® LF17580 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Altura	7.24 inch / 184.00 mm	Gasket Outside Diameter	4.02 inch / 102.00 mm
A Frecuencia 2	ISO 4548-12	Flujo Nominal	1.72 gpm / 6.50 L/min
Diámetro Interior De La Junta	3.70 inch / 94.00 mm	Ruptura Hidrostática Mínima	217.50 psi / 1500.00 kPa
Válvula De Presión	No	Eficiencia De Partículas Primarias	5.80 micron (c) @ 82.6%
Tamaño de rosca	1.00 3/8-16 UNF 2B	Capacity Test Specification	ISO 4548-12
Tipo De Medio	Cellulose		

Applicable Region	North America, Europe, South America, South East Asia, South Pacific

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES