Product Specifications

LF17505



Lube Filter, Spin-On

Fleetguard® LF17505 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Gasket Outside Diameter	4.02 inch / 102.00 mm	Altura	10.24 inch / 260.10 mm
A Frecuencia 2	ISO 4548-12	Flujo Nominal	9.25 gpm / 35.00 L/min
Diámetro Interior De La Junta	3.70 inch / 94.00 mm	Ruptura Hidrostática Mínima	217.50 psi / 1500.00 kPa
Válvula De Presión	No	Eficiencia De Partículas Primarias	30.00 micron (c) @ 95%
Tipo De Medio	Cellulose	Capacity Test Specification	ISO 4548-12
Tamaño de rosca	1.125-16 UNF 2B		

Applicable Region	North America, China, Europe, South America, South East Asia, South Pacific

Product Comments

Compatible with Euro 6 oils

Related Parts

Upgrade Of	LF3321
Is European Version Of	LF3321

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES