Product Specifications

LF3795



Lube Filter, Spin-On

Fleetguard® LF3795 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Tamaño de rosca	3/4-16 UNF 2B	Gasket Outside Diameter	2.83 inch / 71.98 mm
Diámetro Interior De La Junta	2.46 inch / 62.53 mm	Largest Outside Diameter	3.79 inch / 96.20 mm
Altura	3.79 inch / 96.27 mm	Válvula De Presión	Yes
Ruptura Hidrostática Mínima	203.00 psi / 1400.00 kPa	Flujo Nominal	3.17 gpm / 12.00 L/min
Eficiencia De Partículas Primarias	24.60 micron (c) @ 76%	Tipo De Medio	Cellulose

Applicable Region	North America, China, Europe, South America, South East Asia, South Pacific, Mexico and Central America

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa

convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES