Product Specifications

FF5322



Fuel Filter, Spin-On

Fleetguard® FF5322 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Tamaño de rosca	7/8-14 UNF-2B
Diámetro Interior De La Junta	2.46 inch / 62.53 mm
Largest Outside Diameter	3.68 inch / 93.52 mm
A Frecuencia 2	SAE J905
Eficiencia De Partículas Primarias	6.50 micron (c) @ 98.7%
Tipo De Medio	Cellulose

Gasket Outside Diameter	2.83 inch / 71.98 mm
Altura	9.47 inch / 240.54 mm
Tubo Vertical	No
Ruptura Hidrostática Mínima	203.00 psi / 1400.00 kPa
Flujo Nominal	0.84 gpm / 3.17 L/min
Overall Height	9.47 inch / 240.51 mm

Applicable Region	North America, China, Europe, South America, South East Asia, South Pacific, Mexico and Central America

Related Parts

For Upgrade, Use	FF5818

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES