Product Specifications

FS20162



Fuel/Water Separator, Spin-On

Fleetguard® FS20162 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

View product on Fleetguard.com

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES

Specifications

Largest Outside Diameter	4.29 inch / 108.97 mm	Altura	11.31 inch / 287.27 mm
Gasket Outside Diameter	3.55 inch / 90.17 mm	Tipo De Medio	Cellulose
Diámetro Interior De La Junta	3.16 inch / 80.26 mm	Capacity Test Specification	ISO 19438
Flujo Nominal	3.00 gpm / 11.36 lpm	Ruptura Hidrostática Mínima	200.00 psi / 1379.31 kPa
Eficiencia De Partículas Primarias	4.00 micron (c) @ 98.7%		

Applicable Region	North America, Europe, South America, South East Asia, South Pacific

"Fleetguard is a brand of Atmus Filtration Technologies (“Atmus”). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

INSUMIND PERÚ
INSUMOS MINEROS INDUSTRIALES